



OPTICAL FIBER CLEAVER

ISO 9001 Certified

S325A Hand-Held High Precision Cleaver



One-Step Cleaving... In the Palm of your Hands

Key Features

- One-Step Action
- Cleave Anywhere! - In Your Palm or on Your Desktop
- Easy Fiber Loading
- Simple Operation
- High Capacity Waste Fiber Collection
- Durable Design
- Easy Maintenance on-Site

Specifications

Fiber Types	All fiber types, single to 12-fiber ribbons	
Clad Diameter	0.125mm	
Coating Diameter	0.25mm and 0.9mm for single fiber; 0.3mm to 0.4mm thickness for ribbons	
Cleave Length	Single Fiber: Fixed Length - 10 & 16mm Ribbon Fiber: 10mm Fixed Length	Variable Length - 3 to 20mm
Dimensions/Weight	93W x 68D x 52H [mm], 330 grams	

Standard Components

Model	Item	Part Number	Qty
S325A	Main Body	S325X-01	1
	Soft Carrying Case	S325X-02	1
	Normal Fiber Waste Bin	S325X-03	2
	Single Fiber Adapter	S325X-04	1
	Large Capacity Fiber Waste Bin	S325X-05	1
	Operation Manual	FTS-B277	1



Head Office:

6-1, Marunouchi 2-chome,
Chiyoda-ku, Tokyo, 100-8322, Japan
TEL: +81 3 3286 3222
FAX: +81 3 3286 3747
www.furukawa.co.jp
comsales@ho.furukawa.co.jp

Europe:

Furukawa Electric Europe Ltd.
3rd Floor, Newcombe House
43-45 Notting Hill Gate,
London W11 3FE U.K.
TEL: +44 20 7313 5320
FAX: +44 20 7313 5310
www.furukawa.co.uk
sales@furukawa.co.uk

North & South America:

Furukawa America, Inc.
200 Westpark Drive, Suite 190
Peachtree City, GA 30269
TEL: +1 770 487 1234
FAX: +1 770 487 9910
www.FurukawaAmerica.com
splitters@FurukawaAmerica.com

South East Asia:

Furukawa Electric Singapore Pte. Ltd.
10 Anson Road, #25-07/08,
International Plaza, Singapore 079903
Tel: +65 6328 9896
Fax: +65 6224 2362
admin@furukawa.com.sg