

# 150Mbps Wireless N Router

## WF2412



### Features:

- >Wireless N speed up to 150Mbps
- >Multi-wireless modes to expand the wireless network: AP, WDS, AP+WDS, Client, Repeater
- >Easy wireless security encryption with single WPS button
- >Slim body design and internal antenna to save space
- >Quick setup, with built-in management page

### Brief:

The netis WF2412 150Mbps Wireless N Router is a combined wired and wireless device for SOHO network applications. With the ingenious and slim body design, it provides you a perfect choice for home and travel use. This router is compatible with 802.11b/g/n devices and provides the wireless transfer speed up to 150Mbps, offering a better performance on web surfing, emailing, and file sharing. Moreover, it supports multi-wireless modes including AP, WDS, AP+WDS, Repeater, Client, to expand your wireless network easily.

## 150Mbps Wireless N Router

# WF2412

### Specification:

Wireless	
Standard	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 150Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	20dBm (MAX)
Data Transfer Rate	802.11n: 40MHz (150Mbps, 135Mbps, 120Mbps, 90Mbps, 60Mbps, 45Mbps, 30Mbps, 15Mbps) 20MHz (72Mbps, 65Mbps, 57Mbps, 43Mbps, 28Mbps, 21Mbps, 14Mbps, 7Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	AP, WDS, AP+WDS, Repeater, Client, Multiple AP
Wireless Security	64/128-bit WEP WPA-PSK/ WPA2-PSK (TKIP/AES) SSID Broadcast Enable/Disable Wireless MAC Filtering
Hardware	
Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interface	1 * 10/100M Auto MDI/MDIX RJ45 WAN port 4 * 10/100M Auto MDI/MDIX RJ45 LAN port
LED	PWR, WPS, WAN, 1X-4X
Button	Default, WPS
Antenna	1 * internal 4dBi antennas
Power Supply	DC 9V/500mA (Output)
Dimensions(L x W x H )	49 x 88 x 125 mm
Weight	112g
Software	
WAN Type	DHCP (Dynamic IP), PPPoE, Static IP, WISP
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port
QoS	WMM, Bandwidth Control
Access Control	IP/MAC/Domain filtering
VPN Pass-through	PPTP, L2TP, IPSEC
Others	DDNS, Static Routing, WOL, Remote Management, Firmware upgrade
Others	
Certification	FCC, CE, NCC, BSMI
Environment	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Package	1 * WF2412 1 * Power Adapter 1 * Ethernet Cable

### Topological Graph:

