

Switch Flex



Mechanical

Dimensions	122.5 x 107.1 x 28 mm (4.8 x 4.2 x 1.1")
Weight	230 g (8.11 oz)
Enclosure material	Polycarbonate

Hardware

Management interface	Ethernet In-band
Networking interface	(5) GbE RJ45 ports
PoE interface	(4) PoE+ (Pins 1, 2+; 3, 6-)
Total non-blocking throughput	5 Gbps
Power method	PoE++
Power supply	PoE/PoE+ (Pins 1, 2+; 3, 6-) PoE++ (Pins 1, 2+; 3, 6- and 4, 5+; 7, 8-) 50W/60W PoE adapter (not included)
Supported voltage range	PoE: 44–57V DC PoE+/PoE++: 50–57V DC
Max. power consumption	5W (Excluding PoE output)
Total available PoE	46W* <small>*When powered with a PoE++ switch or a 60W PoE adapter (sold separately).</small>
Max. PoE wattage per port by PSE	25W
Voltage range PoE mode	44–57V
Voltage range PoE+ mode	50–57V
ESD/EMP protection	Air/contact: ±16kV
Button	Factory reset
Operating temperature	46W PoE output: -40 to 55° C (-40 to 131° F) 25W PoE output: -40 to 65° C (-40 to 149° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

LEDs

System	Status
Ethernet	PoE Speed/link/activity
PoE	Link/activity

