

Product Datasheet

Product ID: TP-ADAPTOR-R5AC



TwistPort™ Adaptor for Rocket AC

ADAPTOR FOR ROCKET™ 5AC-LITE

The TwistPort™ Adaptor for Rocket 5AC-Lite makes the Rocket™ compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Connecting and disconnecting the Rocket™ 5AC-Lite into the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

| | |
|--------------------|--|
| Antenna Connection | TwistPort - Quick Locking Waveguide Port |
| Radio Connection | 2x Slide-On RP-SMA |
| Materials | Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic |
| Flame Rating | UL 94 HB |
| Temperature | -40°C to +60°C (-40°F to +140°F) |
| Wind Survival | 160 km/h |
| Weight | 0.4 Kg / 0.9 lbs – single unit 0.5 Kg / 1.1 lbs – single unit incl. package 11.5 Kg / 25 lbs – carton (20 units) |
| Single Unit | Retail Box: 12.8 × 13.6 × 11.7 cm |
| 20 Units | Carton Box: 29 × 60.5 × 28.5 cm |

PERFORMANCE

| | |
|---------------------------|-------------------|
| Frequency Range | 5400 - 5900 MHz |
| Polarization | Dual Linear H + V |
| Cross Pol Isolation (Min) | 29 dB |
| VSWR Max | 1.8 |
| VSWR Typical | 1.4 |
| Impedance 50 Ohm | 50 Ohm |
| Isolation Between Ports | 37 dB |

COMPATIBLE WIRELESS PLATFORMS

| | |
|--------------------|--|
| RF elements® | any Symmetrical Horn TP Antenna, any UltraDish™ TP Antenna |
| Ubiquiti Networks™ | Rocket™ 5AC-Lite |

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

